

VpCI®-423





PRODUCT DESCRIPTION

VpCl[®]-423 is a water-based gel that effectively removes rust and oxides from steel, iron, brass, and copper. When used as recommended, VpCl[®]-423 will not adversely affect most paints, plastics, wood, textiles, ceramics, or rubber. VpCl[®]-423 is formulated to cling on vertical and overhead surfaces for rust and oxide removal in difficult-to-reach spaces.

VpCl[®]-423 contains flash corrosion inhibitors to prevent flash corrosion during the rust and oxide removal process. After rust removal, rinse the area thoroughly with water, then use Cortec[®] VpCl[®]-414 or similar alkaline cleaners to ensure a clean, corrosion free metal surface.

 $VpCI^{\circledast}\mbox{-}423$ is NSF (A3) registered, acceptable for use for indirect food contact. It contains 91% USDA certified biobased content and qualifies for Mandatory Federal Purchasing in the USDA BioPreferred^{\circledast}

FEATURES

- Prevents flash rusting
- No adverse effects on most paints, plastics, wood, textiles, ceramics, and rubbers
- Formulated for rust and oxide removal on vertical and overhead surfaces
- NSF (A3) registered. Acceptable for use as an acid cleaner in and around food processing areas for indirect food contact.
- Contains 91% USDA certified biobased content
- NSN 6850-01-482-4536

TYPICAL APPLICATIONS

- In-process rust removal for parts and metal stock
- Rust removal in hard-to-reach, vertical, and overhead locations
- Automotive, marine, and manufacturing equipment

APPLICATION

VpCl[®]-423 can be applied using conventional or airless spray equipment or by brush. Remove loose or flaking rust and then apply VpCl[®]-423 to the surface. Let the product stand for 10-15 minutes and rinse with Cortec[®] VpCl[®]-414 or a similar alkaline cleaner. Retreat rust as necessary (heavy rust may take more than one treatment).

PHYSICAL PROPERTIES

Appearance	Dark brown gel	
pH (Neat)	2.3	
Density	9.6-10.0 lb/gal (1.16-1.19 kg/l)	

PACKAGING AND STORAGE

VpCl[®]-423 is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes, and bulk. Store in a heated warehouse to avoid freezing.



Toxicological Testing Results

Species	NOEC/LOEC ppm	48-hrs LC50 * ppm
M. beryllina	100/1000	316
M. bahla	100/1000	316

* LC50/EC50-50% of Lethal concetration/50% of Effective Concetration respectively.

FOR INDUSTRIAL USE ONLY **KEEP OUT OF REACH OF CHILDREN KEEP CONTAINER TIGHTLY CLOSED** NOT FOR INTERNAL CONSUMPTION **CONSULT SAFETY DATA SHEET FOR MORE INFORMATION**

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products. BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE.

AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



4119 White Bear Parkway, St. Paul, MN 55110 USA Phone (651) 429-1100, Fax (651) 429-1122 Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com http://www.cortecvci.com

Printed on recycled paper 🏹 100% post consumer

Revised: 08/14/17. Supercedes: 08/13/13. ©Cortec Corporation 2002-2016 of Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the writted authorization of Cortec Corporation is strictly prohibited. 2016, ©Cortec Corp. ISO accreditation applies to Cortec's processes only.

Distributed by: